

# R6RS: Scheme

Version 8.12.900

April 24, 2024

The The Revised<sup>6</sup> Report on the Algorithmic Language Scheme defines a dialect of Scheme. We use *R<sup>6</sup>RS* to refer to both the standard and the language defined by the standard.

R<sup>6</sup>RS defines both *libraries* and *top-level programs*. Both correspond to Racket *modules* (see §6 “Modules”). That is, although R<sup>6</sup>RS defines top-level programs as entry points, you can just as easily treat a library as an entry point when using Racket. The only difference is that an R<sup>6</sup>RS top-level program cannot export any bindings to other modules.

See §23 “Dialects of Racket and Scheme” for general information about different dialects of Scheme within Racket.

# Contents

<b>1</b>	<b>Using R<sup>6</sup>RS with DrRacket</b>	<b>4</b>
<b>2</b>	<b>Running Top-Level Programs</b>	<b>5</b>
<b>3</b>	<b>Installing Libraries</b>	<b>6</b>
<b>4</b>	<b>R<sup>6</sup>RS Module Language</b>	<b>8</b>
4.1	Using R <sup>6</sup> RS . . . . .	8
4.2	The Implementation of R <sup>6</sup> RS . . . . .	8
<b>5</b>	<b>Libraries and Collections</b>	<b>9</b>
<b>6</b>	<b>Language Interoperability</b>	<b>10</b>
<b>7</b>	<b>R<sup>6</sup>RS Conformance</b>	<b>11</b>
<b>8</b>	<b>R<sup>6</sup>RS Libraries</b>	<b>13</b>
8.1	( <code>rnrs base (6)</code> ): Base . . . . .	13
8.2	( <code>rnrs unicode (6)</code> ): Unicode . . . . .	13
8.3	( <code>rnrs bytevectors (6)</code> ): Bytevectors . . . . .	13
8.4	( <code>rnrs lists (6)</code> ): List utilities . . . . .	13
8.5	( <code>rnrs sorting (6)</code> ): Sorting . . . . .	13
8.6	( <code>rnrs control (6)</code> ): Control Structures . . . . .	13
8.7	( <code>rnrs records syntactic (6)</code> ): Records: Syntactic . . . . .	14
8.8	( <code>rnrs records procedural (6)</code> ): Records: Procedural . . . . .	14
8.9	( <code>rnrs records inspection (6)</code> ): Records: Inspection . . . . .	14
8.10	( <code>rnrs exceptions (6)</code> ): Exceptions . . . . .	14

8.11	( <code>rnrs conditions (6)</code> ): Conditions . . . . .	14
8.12	( <code>rnrs io ports (6)</code> ): I/O: Ports . . . . .	14
8.13	( <code>rnrs io simple (6)</code> ): I/O: Simple . . . . .	15
8.14	( <code>rnrs files (6)</code> ): File System . . . . .	15
8.15	( <code>rnrs programs (6)</code> ): Command-line Access and Exit Values . . . . .	15
8.16	( <code>rnrs arithmetic fixnums (6)</code> ): Arithmetic: Fixnums . . . . .	15
8.17	( <code>rnrs arithmetic flonums (6)</code> ): Arithmetic: Flonums . . . . .	15
8.18	( <code>rnrs arithmetic bitwise (6)</code> ): Arithmetic: Bitwise . . . . .	15
8.19	( <code>rnrs syntax-case (6)</code> ): Syntax-Case . . . . .	16
8.20	( <code>rnrs hashtables (6)</code> ): Hashtables . . . . .	16
8.21	( <code>rnrs enums (6)</code> ): Enumerations . . . . .	16
8.22	( <code>rnrs eval (6)</code> ): Eval . . . . .	16
8.23	( <code>rnrs mutable-pairs (6)</code> ): Mutable Pairs . . . . .	16
8.24	( <code>rnrs mutable-strings (6)</code> ): Mutable Strings . . . . .	16
8.25	( <code>rnrs r5rs (6)</code> ): R5RS Compatibility . . . . .	17
	<b>Index</b> . . . . .	<b>18</b>
	<b>Index</b> . . . . .	<b>18</b>

## 1 Using R<sup>6</sup>RS with DrRacket

To run an R<sup>6</sup>RS program with DrRacket choose Use language declared in source from the language dialog box and add the following line to the top of your program. `#!r6rs`.

Here is a small example R<sup>6</sup>RS program that will work in DrRacket.

```
#!r6rs
(import (rnrs lists (6))
        (rnrs base (6))
        (rnrs io simple (6)))
(display (find even? '(3 1 4 1 5 9)))
```

## 2 Running Top-Level Programs

To run a top-level program, either:

- Use the `plt-r6rs` executable, supplying the file that contains the program on the command line:

```
plt-r6rs <program-file>
```

Additional command-line arguments are propagated as command-line arguments to the program (accessed via [command-line](#)).

To compile the file to bytecode (to speed future runs of the program), use `plt-r6rs` with the `--compile` flag:

```
plt-r6rs --compile <program-file>
```

The bytecode file is written in a "compiled" sub-directory next to *<program-file>*.

For example, if `hi.sps` contains

```
(import (rnrs))
(display "hello\n")
```

then

```
plt-r6rs hi.sps
```

prints "hello."

- Prefix the program with `#!r6rs`, which counts as a comment from the R<sup>6</sup>RS perspective, but is a synonym for `#lang r6rs` from the Racket perspective. Such files can be run like any other Racket module, such as using `racket`:

```
racket <program-file>
```

or using DrRacket. The file can also be compiled to bytecode using `raco make`:

```
raco make <program-file>
```

For example, if `hi.sps` contains

```
#!r6rs
(import (rnrs))
(display "hello\n")
```

then

```
racket hi.sps
```

prints "hello." Similarly, opening `hi.sps` in DrRacket and clicking Run prints "hello" within the DrRacket interactions window.

### 3 Installing Libraries

To reference an R<sup>6</sup>RS library from a top-level program or another library, it must be installed as a collection-based library in Racket.

One way to produce an R<sup>6</sup>RS installed library is to create in a collection a file that starts with `#!r6rs` and that contains a `library` form. For example, the following file might be created in a "hello.sls" file within a "examples" collection directory:

```
#!r6rs
(library (examples hello)
  (export greet)
  (import (rnrs)))

(define (greet)
  (display "hello\n"))
```

Alternately, the `plt-r6rs` executable with the `--install` flag accepts a sequence of `library` declarations and installs them into separate files in a collection directory, based on the declared name of each library:

```
plt-r6rs --install <libraries-file>
```

By default, libraries are installed into the user-specific collection directory (see `find-user-collects-dir`). The `--all-users` flag causes the libraries to be installed into the main installation, instead (see `find-collects-dir`):

```
plt-r6rs --install --all-users <libraries-file>
```

You may as well specify an arbitrary collections directory by using the `--collections` flag:

```
plt-r6rs --install --collections <directory> <libraries-file>
```

See §5 “Libraries and Collections” for information on how R<sup>6</sup>RS library names are turned into collection-based module paths, which determines where the files are written. Libraries installed by `plt-r6rs --install` are automatically compiled to bytecode form.

One final option is to supply a `++path` flag to `plt-r6rs`. A path added with `++path` extends the set of directories that are searched to find a collection (i.e., it sets `current-library-collection-paths`). If `<dir>` contains "duck" and "cow" sub-directories with "duck/feather.sls" and "cow/bell.sls", and if each file is an R<sup>6</sup>RS library prefixed with `#!r6rs`, then `plt-r6rs ++path <dir>` directs the R<sup>6</sup>RS library references `(duck feather)` and `(cow bell)` to the files. Note that this technique does not support accessing "duck.sls" directly within `<dir>`, since the library reference `(duck)` is treated like `(duck main)` for finding the library, as explained in §5 “Libraries and Collections”. Multiple paths

can be provided with multiple uses of ++path; the paths are searched in order, and before the installation's collections.

## 4 R<sup>6</sup>RS Module Language

```
#lang r6rs      package: r6rs-lib
```

The `r6rs` language is usually used in the form `#!r6rs`, which is equivalent to `#lang r6rs` and is also valid R<sup>6</sup>RS syntax.

### 4.1 Using R<sup>6</sup>RS

See §1 “Using R<sup>6</sup>RS with DrRacket”, §2 “Running Top-Level Programs”, and §3 “Installing Libraries” for more information on writing and running R<sup>6</sup>RS programs with Racket.

### 4.2 The Implementation of R<sup>6</sup>RS

The R<sup>6</sup>RS language is itself implemented as a module within Racket. The details of that implementation, as provided in this section, are not normally relevant to programmers using R<sup>6</sup>RS; see the links in §4.1 “Using R<sup>6</sup>RS”, instead. The details may be relevant to programmers who are developing new tools or deriving variants of R<sup>6</sup>RS within Racket.

As a Racket module, the `r6rs` module language provides only a `#!/module-begin` binding, which is used to process the entire body of a Racket module (see `module`). The `#!/module-begin` binding from `r6rs` allows the body of a module to use the syntax of either a R<sup>6</sup>RS library or a R<sup>6</sup>RS top-level program.

```
(#!/module-begin
  (library library-name
    (export export-spec ...)
    (import import-spec ...)
    library-body ...))
(#!/module-begin
  (import import-spec ...)
  program-body ...)
```

An `r6rs` module that contains a single `library` form defines an R<sup>6</sup>RS library, while a module body that starts with an `import` form defines an R<sup>6</sup>RS top-level program.

The `library`, `export`, and `import` identifiers are not exported by the `r6rs` library; they are recognized through equivalence to unbound identifiers.



## 5 Libraries and Collections

An R<sup>6</sup>RS library name is sequence of symbols, optionally followed by a version as a sequence of exact, non-negative integers. Roughly, such a name is converted to a Racket module pathname (see §6.3 “Module Paths”) by concatenating the symbols with a `/` separator, and then appending the version integers each with a preceding `-`. As a special case, when an R<sup>6</sup>RS path contains a single symbol (optionally followed by a version), a `main` symbol is effectively inserted after the initial symbol. See below for further encoding considerations.

When an R<sup>6</sup>RS library or top-level program refers to another library, it can supply version constraints rather than naming a specific version. Version constraints are always resolved at compile time by searching the set of installed files.

In addition, when an R<sup>6</sup>RS library path is converted, a file extension is selected at compile time based on installed files. The search order for file extensions is `".mzscheme.ss"`, `".mzscheme.sls"`, `".ss"`, `".sls"`, and `".rkt"`. When resolving version constraints, these extensions are all tried when looking for matches.

To ensure that all R<sup>6</sup>RS library names can be converted to a unique and distinct library module path, the following conversions are applied to each symbol before concatenating them:

- The symbol is encoded using UTF-8, and the resulting bytes are treated as Latin-1 encoded characters. ASCII letters, digits, `+`, `=`, and `_` are left as-is; other characters are replaced by `%` followed by two lowercase hexadecimal digits. Note that UTF-8 encodes ASCII letters, digits, etc. as themselves, so typical library names correspond to readable module paths.
- If the R<sup>6</sup>RS library reference has two symbol elements and the second one is `main` followed by any number of underscores, then an extra underscore is added to that symbol. This conversion avoids a collision between an explicit `main` and the implicit `main` when a library path has a single symbol element.

Examples (assuming a typical Racket installation):

<code>(rnrs io simple (6))</code>	means	<code>(lib "rnrs/io/simple-6.rkt")</code>
<code>(rnrs)</code>	means	<code>(lib "rnrs/main-6.rkt")</code>
<code>(rnrs main)</code>	means	<code>(lib "rnrs/main_.rkt")</code>
<code>(rnrs (6))</code>	means	<code>(lib "rnrs/main-6.rkt")</code>
<code>(racket base)</code>	means	<code>(lib "racket/base.rkt")</code>
<code>(achtung!)</code>	means	<code>(lib "achtung%21/main.rkt")</code>
<code>(funco new-λ)</code>	means	<code>(lib "funco/new-%ce%bb.rkt")</code>

## 6 Language Interoperability

Using the conversion rules in §5 “Libraries and Collections”, and R<sup>6</sup>RS library can refer to modules that are implemented in other dialects supported by Racket, and other Racket modules can refer to libraries that are implemented in R<sup>6</sup>RS.

Beware that a *pair* in R<sup>6</sup>RS corresponds to a *mutable pair* in `racket/base`. Otherwise, R<sup>6</sup>RS libraries and `racket/base` share the same datatype for numbers, characters, strings, bytevectors (a.k.a. byte strings), vectors, and so on. Hash tables are different. Input and output ports from `racket/base` can be used directly as binary ports with R<sup>6</sup>RS libraries, and all R<sup>6</sup>RS ports can be used as ports in `racket/base` programs, but only textual ports created via R<sup>6</sup>RS libraries can be used by other R<sup>6</sup>RS operations that expect textual ports.

## 7 R<sup>6</sup>RS Conformance

Racket's R<sup>6</sup>RS support does not conform with the standard in several known ways:

- When guard catches an exception that no clause matches, the exception is re-[raised](#) without restoring the continuation to the one that raised the exception.

This difference can be made visible using [dynamic-wind](#). According to R<sup>6</sup>RS, the following program should print “in” and “out” twice, but each prints once using Racket:

```
(guard (exn [(equal? exn 5) 'five]))
  (guard (exn [(equal? exn 6) 'six]))
    (dynamic-wind
      (lambda () (display "in") (newline))
      (lambda () (raise 5))
      (lambda () (display "out") (newline))))
```

Along similar lines, continuation capture and invocation within an exception handler is restricted. Unless the exception is raised through [raise-continuable](#), a handler can escape only through a continuation that is a tail of the current continuation, and a continuation captured within the handler cannot be invoked after control escapes from the raise.

The initial exception handler does not return for non-[&serious](#) conditions, but [raise](#) and [raise-continuable](#) both install an uncaught-exception handler (via [parameterize](#) and [uncaught-exception-handler](#)) to one that returns for non-[&serious](#) conditions.

- Inexact numbers are printed without a precision indicator, and precision indicators are ignored on input (e.g., [0.5|7](#) is read the same as [0.5](#)).
- Word boundaries for [string-downcase](#), [string-upcase](#), and [string-titlecase](#) are not determined as specified by Unicode Standard Annex #29.
- A custom textual port must represent positions using integers, and the positions must correspond to bytes in a UTF-8 encoding of the port's data. For custom ports (byte or character) that support both input and output, beware that buffered input can create a mismatch between the position implemented by the custom procedures and the port's current position; the result from a custom position procedure is automatically adjusted to account for buffering, and setting the port's position flushes all buffered bytes, but writing after a read does *not* automatically reset the port's position to counteract the effects of buffering.
- The bindings in a namespace produced by [null-environment](#) or [scheme-report-environment](#) correspond to R<sup>5</sup>RS bindings instead of R<sup>6</sup>RS bindings. In particular, [=>](#), [else](#), [\\_](#), and [...](#) are not bound.

- Bindings for `#!/datum`, `#!/app`, `#!/top`, and `#!/top-interaction` are imported into every library and program, and at every phase level for which the library or program has imports.

Changed in version 6.0.1.4: When an identifier bound by `letrec` or `letrec*` is referenced before it is initialized, an exception is raised, instead of producing `#!/undefined`.

## 8 R<sup>6</sup>RS Libraries

### 8.1 `(rnrs base (6))`: Base

```
(require rnrs/base-6)      package: r6rs-lib
```

Original specification: Base

### 8.2 `(rnrs unicode (6))`: Unicode

```
(require rnrs/unicode-6)   package: r6rs-lib
```

Original specification: Unicode

### 8.3 `(rnrs bytevectors (6))`: Bytevectors

```
(require rnrs/bytevectors-6) package: r6rs-lib
```

Original specification: Bytevectors

### 8.4 `(rnrs lists (6))`: List utilities

```
(require rnrs/lists-6)     package: r6rs-lib
```

Original specification: List utilities

### 8.5 `(rnrs sorting (6))`: Sorting

```
(require rnrs/sorting-6)   package: r6rs-lib
```

Original specification: Sorting

### 8.6 `(rnrs control (6))`: Control Structures

```
(require rnrs/control-6)   package: r6rs-lib
```

Original specification: Control Structures

### 8.7 `(rnrs records syntactic (6))`: Records: Syntactic

`(require rnrs/records/syntactic-6)` package: `r6rs-lib`

Original specification: Records: Syntactic

### 8.8 `(rnrs records procedural (6))`: Records: Procedural

`(require rnrs/records/procedural-6)` package: `r6rs-lib`

Original specification: Records: Procedural

### 8.9 `(rnrs records inspection (6))`: Records: Inspection

`(require rnrs/records/inspection-6)` package: `r6rs-lib`

Original specification: Records: Inspection

### 8.10 `(rnrs exceptions (6))`: Exceptions

`(require rnrs/exceptions-6)` package: `r6rs-lib`

Original specification: Exceptions

See also §7 “R<sup>6</sup>RS Conformance”.

### 8.11 `(rnrs conditions (6))`: Conditions

`(require rnrs/conditions-6)` package: `r6rs-lib`

Original specification: Conditions

### 8.12 `(rnrs io ports (6))`: I/O: Ports

`(require rnrs/io/ports-6)` package: `r6rs-lib`

Original specification: I/O: Ports

### 8.13 `(rnrs io simple (6))`: I/O: Simple

`(require rnrs/io/simple-6)`      package: `r6rs-lib`

Original specification: I/O: Simple

### 8.14 `(rnrs files (6))`: File System

`(require rnrs/files-6)`      package: `r6rs-lib`

Original specification: File System

### 8.15 `(rnrs programs (6))`: Command-line Access and Exit Values

`(require rnrs/programs-6)`      package: `r6rs-lib`

Original specification: Command-line Access and Exit Values

### 8.16 `(rnrs arithmetic fixnums (6))`: Arithmetic: Fixnums

`(require rnrs/arithmetic/fixnums-6)`      package: `r6rs-lib`

Original specification: Arithmetic: Fixnums

### 8.17 `(rnrs arithmetic flonums (6))`: Arithmetic: Flonums

`(require rnrs/arithmetic/flonums-6)`      package: `r6rs-lib`

Original specification: Arithmetic: Flonums

### 8.18 `(rnrs arithmetic bitwise (6))`: Arithmetic: Bitwise

`(require rnrs/arithmetic/bitwise-6)`      package: `r6rs-lib`

Original specification: Arithmetic: Bitwise

### 8.19 `(nnrs syntax-case (6))`: Syntax-Case

```
(require nnrs/syntax-case-6)      package: r6rs-lib
```

Original specification: Syntax-Case

### 8.20 `(nnrs hashtables (6))`: Hashtables

```
(require nnrs/hashtables-6)      package: r6rs-lib
```

Original specification: Hashtables

A hashtable is a dictionary in the sense of `racket/dict`, and hash table operations interact with threads in the same way for hash tables created with `make-hash` (e.g., `hashtable-ref` and `hashtable-set!` are thread-safe).

### 8.21 `(nnrs enums (6))`: Enumerations

```
(require nnrs/enums-6)           package: r6rs-lib
```

Original specification: Enumerations

### 8.22 `(nnrs eval (6))`: Eval

```
(require nnrs/eval-6)           package: r6rs-lib
```

Original specification: Eval

### 8.23 `(nnrs mutable-pairs (6))`: Mutable Pairs

```
(require nnrs/mutable-pairs-6)   package: r6rs-lib
```

Original specification: Mutable Pairs

### 8.24 `(nnrs mutable-strings (6))`: Mutable Strings

```
(require nnrs/mutable-strings-6) package: r6rs-lib
```

Original specification: Mutable Strings



## 8.25 `(rnrs r5rs (6))`: R5RS Compatibility

`(require rnrs/r5rs-6)`      `package: r6rs-lib`

Original specification: R5RS Compatibility

See also §7 “R<sup>6</sup>RS Conformance”.

## Index

`#!/module-begin`, 8  
`&assertion`, 14  
`&condition`, 14  
`&error`, 14  
`&i/o`, 14  
`&i/o-decoding`, 14  
`&i/o-encoding`, 14  
`&i/o-file-already-exists`, 14  
`&i/o-file-does-not-exist`, 14  
`&i/o-file-is-read-only`, 14  
`&i/o-file-protection`, 14  
`&i/o-filename`, 14  
`&i/o-invalid-position`, 14  
`&i/o-port`, 14  
`&i/o-read`, 14  
`&i/o-write`, 14  
`&implementation-restriction`, 14  
`&irritants`, 14  
`&lexical`, 14  
`&message`, 14  
`&no-infinities`, 15  
`&no-nans`, 15  
`&non-continuable`, 14  
`&serious`, 14  
`&syntax`, 14  
`&undefined`, 14  
`&violation`, 14  
`&warning`, 14  
`&who`, 14  
`(rnrs arithmetic bitwise (6))`: Arithmetic: Bitwise, 15  
`(rnrs arithmetic fixnums (6))`: Arithmetic: Fixnums, 15  
`(rnrs arithmetic flonums (6))`: Arithmetic: Flonums, 15  
`(rnrs base (6))`: Base, 13  
`(rnrs bytevectors (6))`: Bytevectors, 13  
`(rnrs conditions (6))`: Conditions, 14  
`(rnrs control (6))`: Control Structures, 13  
`(rnrs enums (6))`: Enumerations, 16  
`(rnrs eval (6))`: Eval, 16  
`(rnrs exceptions (6))`: Exceptions, 14  
`(rnrs files (6))`: File System, 15  
`(rnrs hashtables (6))`: Hashtables, 16  
`(rnrs io ports (6))`: I/O: Ports, 14  
`(rnrs io simple (6))`: I/O: Simple, 15  
`(rnrs lists (6))`: List utilities, 13  
`(rnrs mutable-pairs (6))`: Mutable Pairs, 16  
`(rnrs mutable-strings (6))`: Mutable Strings, 16  
`(rnrs programs (6))`: Command-line Access and Exit Values, 15  
`(rnrs r5rs (6))`: R5RS Compatibility, 17  
`(rnrs records inspection (6))`: Records: Inspection, 14  
`(rnrs records procedural (6))`: Records: Procedural, 14  
`(rnrs records syntactic (6))`: Records: Syntactic, 14  
`(rnrs sorting (6))`: Sorting, 13  
`(rnrs syntax-case (6))`: Syntax-Case, 16  
`(rnrs unicode (6))`: Unicode, 13  
`*`, 13  
`+`, 13  
`++path`, 6  
`-`, 13  
`...`, 13  
`...`, 16  
`/`, 13  
`<`, 13  
`<=`, 13  
`=`, 13  
`=>`, 13  
`=>`, 14  
`>`, 13  
`>=`, 13  
`_`, 13  
`_`, 16  
`abs`, 13

[acos](#), 13  
[and](#), 13  
[angle](#), 13  
[append](#), 13  
[apply](#), 13  
[asin](#), 13  
[assert](#), 13  
[assertion-violation](#), 13  
[assertion-violation?](#), 14  
[assoc](#), 13  
[assp](#), 13  
[assq](#), 13  
[assv](#), 13  
[atan](#), 13  
[begin](#), 13  
[binary-port?](#), 14  
[bitwise-and](#), 15  
[bitwise-arithmetic-shift](#), 15  
[bitwise-arithmetic-shift-left](#), 15  
[bitwise-arithmetic-shift-right](#), 15  
[bitwise-bit-count](#), 15  
[bitwise-bit-field](#), 15  
[bitwise-bit-set?](#), 15  
[bitwise-copy-bit](#), 15  
[bitwise-copy-bit-field](#), 15  
[bitwise-first-bit-set](#), 15  
[bitwise-if](#), 15  
[bitwise-ior](#), 15  
[bitwise-length](#), 15  
[bitwise-not](#), 15  
[bitwise-reverse-bit-field](#), 15  
[bitwise-rotate-bit-field](#), 15  
[bitwise-xor](#), 15  
[boolean=?](#), 13  
[boolean?](#), 13  
[bound-identifier=?](#), 16  
[buffer-mode](#), 14  
[buffer-mode?](#), 14  
[bytevector->sint-list](#), 13  
[bytevector->string](#), 14  
[bytevector->u8-list](#), 13  
[bytevector->uint-list](#), 13  
[bytevector-copy](#), 13  
[bytevector-copy!](#), 13  
[bytevector-fill!](#), 13  
[bytevector-ieee-double-native-ref](#), 13  
[bytevector-ieee-double-native-set!](#), 13  
[bytevector-ieee-double-ref](#), 13  
[bytevector-ieee-single-native-ref](#), 13  
[bytevector-ieee-single-native-set!](#), 13  
[bytevector-ieee-single-ref](#), 13  
[bytevector-length](#), 13  
[bytevector-s16-native-ref](#), 13  
[bytevector-s16-native-set!](#), 13  
[bytevector-s16-ref](#), 13  
[bytevector-s16-set!](#), 13  
[bytevector-s32-native-ref](#), 13  
[bytevector-s32-native-set!](#), 13  
[bytevector-s32-ref](#), 13  
[bytevector-s32-set!](#), 13  
[bytevector-s64-native-ref](#), 13  
[bytevector-s64-native-set!](#), 13  
[bytevector-s64-ref](#), 13  
[bytevector-s64-set!](#), 13  
[bytevector-s8-ref](#), 13  
[bytevector-s8-set!](#), 13  
[bytevector-sint-ref](#), 13  
[bytevector-sint-set!](#), 13  
[bytevector-u16-native-ref](#), 13  
[bytevector-u16-native-set!](#), 13  
[bytevector-u16-ref](#), 13  
[bytevector-u16-set!](#), 13  
[bytevector-u32-native-ref](#), 13  
[bytevector-u32-native-set!](#), 13  
[bytevector-u32-ref](#), 13  
[bytevector-u32-set!](#), 13  
[bytevector-u64-native-ref](#), 13  
[bytevector-u64-native-set!](#), 13  
[bytevector-u64-ref](#), 13  
[bytevector-u64-set!](#), 13

bytevector-u8-ref, 13	char<?, 13
bytevector-u8-set!, 13	char=?, 13
bytevector-uint-ref, 13	char>=?, 13
bytevector-uint-set!, 13	char>?, 13
bytevector=?, 13	char?, 13
bytevector?, 13	close-input-port, 15
caar, 13	close-output-port, 15
cadr, 13	close-port, 14
call-with-bytevector-output-port,	command-line, 15
14	complex?, 13
call-with-current-continuation, 13	cond, 13
call-with-input-file, 15	condition, 14
call-with-output-file, 15	condition-accessor, 14
call-with-port, 14	condition-irritants, 14
call-with-string-output-port, 14	condition-message, 14
call-with-values, 13	condition-predicate, 14
call/cc, 13	condition-who, 14
car, 13	condition?, 14
case, 13	cons, 13
case-lambda, 13	cons*, 13
cdddar, 13	cos, 13
cddddr, 13	current-error-port, 14
cdr, 13	current-input-port, 14
ceiling, 13	current-output-port, 14
char->integer, 13	datum->syntax, 16
char-alphabetic?, 13	define, 13
char-ci<=?, 13	define-condition-type, 14
char-ci<?, 13	define-enumeration, 16
char-ci=?, 13	define-record-type, 14
char-ci>=?, 13	define-syntax, 13
char-ci>?, 13	delay, 17
char-downcase, 13	delete-file, 15
char-foldcase, 13	denominator, 13
char-general-category, 13	display, 15
char-lower-case?, 13	div, 13
char-numeric?, 13	div-and-mod, 13
char-title-case?, 13	div0, 13
char-titlecase, 13	div0-and-mod0, 13
char-upcase, 13	do, 13
char-upper-case?, 13	dynamic-wind, 13
char-whitespace?, 13	else, 13
char<=?, 13	else, 14

- endianness, 13
- enum-set->list, 16
- enum-set-complement, 16
- enum-set-constructor, 16
- enum-set-difference, 16
- enum-set-indexer, 16
- enum-set-intersection, 16
- enum-set-member?, 16
- enum-set-projection, 16
- enum-set-subset?, 16
- enum-set-union, 16
- enum-set-universe, 16
- enum-set=?, 16
- environment, 16
- eof-object, 14
- eof-object?, 14
- eol-style, 14
- eq?, 13
- equal-hash, 16
- equal?, 13
- eqv?, 13
- error, 13
- error-handling-mode, 14
- error?, 14
- eval, 16
- even?, 13
- exact, 13
- exact->inexact, 17
- exact-integer-sqrt, 13
- exact?, 13
- exists, 13
- exit, 15
- exp, 13
- expt, 13
- fields, 14
- file-exists?, 15
- file-options, 14
- filter, 13
- find, 13
- finite?, 13
- fixnum->flonum, 15
- fixnum-width, 15
- fixnum?, 15
- fl\*, 15
- fl+, 15
- fl-, 15
- fl/, 15
- fl<=?, 15
- fl<?, 15
- fl=?, 15
- fl>=?, 15
- fl>?, 15
- flabs, 15
- flacos, 15
- flasin, 15
- flatan, 15
- flceiling, 15
- flcos, 15
- fldenominator, 15
- fldiv, 15
- fldiv-and-mod, 15
- fldiv0, 15
- fldiv0-and-mod0, 15
- fleven?, 15
- flexp, 15
- flexpt, 15
- flfinite?, 15
- flfloor, 15
- flinfinite?, 15
- flinteger?, 15
- fllog, 15
- flmax, 15
- flmin, 15
- flmod, 15
- flmod0, 15
- flnan?, 15
- flnegative?, 15
- flnumerator, 15
- flodd?, 15
- flonum?, 15
- floor, 13
- flpositive?, 15
- flround, 15
- flsin, 15

<code>flsqrt</code> , 15	<code>fxmod</code> , 15
<code>fltan</code> , 15	<code>fxmod0</code> , 15
<code>fltruncate</code> , 15	<code>fxnegative?</code> , 15
<code>flush-output-port</code> , 14	<code>fxnot</code> , 15
<code>flzero?</code> , 15	<code>fxodd?</code> , 15
<code>fold-left</code> , 13	<code>fxpositive?</code> , 15
<code>fold-right</code> , 13	<code>fxreverse-bit-field</code> , 15
<code>for-all</code> , 13	<code>fxrotate-bit-field</code> , 15
<code>for-each</code> , 13	<code>fxxor</code> , 15
<code>force</code> , 17	<code>fxzero?</code> , 15
<code>free-identifier=?</code> , 16	<code>gcd</code> , 13
<code>fx*</code> , 15	<code>generate-temporaries</code> , 16
<code>fx*/carry</code> , 15	<code>get-bytevector-all</code> , 14
<code>fx+</code> , 15	<code>get-bytevector-n</code> , 14
<code>fx+/carry</code> , 15	<code>get-bytevector-n!</code> , 14
<code>fx-</code> , 15	<code>get-bytevector-some</code> , 14
<code>fx-/carry</code> , 15	<code>get-char</code> , 14
<code>fx&lt;=?</code> , 15	<code>get-datum</code> , 14
<code>fx&lt;?</code> , 15	<code>get-line</code> , 14
<code>fx=?</code> , 15	<code>get-string-all</code> , 14
<code>fx&gt;=?</code> , 15	<code>get-string-n</code> , 14
<code>fx&gt;?</code> , 15	<code>get-string-n!</code> , 14
<code>fxand</code> , 15	<code>get-u8</code> , 14
<code>fxarithmetic-shift</code> , 15	<code>greatest-fixnum</code> , 15
<code>fxarithmetic-shift-left</code> , 15	<code>guard</code> , 14
<code>fxarithmetic-shift-right</code> , 15	<code>hashtable-clear!</code> , 16
<code>fxbit-count</code> , 15	<code>hashtable-contains?</code> , 16
<code>fxbit-field</code> , 15	<code>hashtable-copy</code> , 16
<code>fxbit-set?</code> , 15	<code>hashtable-delete!</code> , 16
<code>fxcopy-bit</code> , 15	<code>hashtable-entries</code> , 16
<code>fxcopy-bit-field</code> , 15	<code>hashtable-equivalence-function</code> , 16
<code>fxdiv</code> , 15	<code>hashtable-hash-function</code> , 16
<code>fxdiv-and-mod</code> , 15	<code>hashtable-keys</code> , 16
<code>fxdiv0</code> , 15	<code>hashtable-mutable?</code> , 16
<code>fxdiv0-and-mod0</code> , 15	<code>hashtable-ref</code> , 16
<code>fxeven?</code> , 15	<code>hashtable-set!</code> , 16
<code>fxfirst-bit-set</code> , 15	<code>hashtable-size</code> , 16
<code>fxif</code> , 15	<code>hashtable-update!</code> , 16
<code>fxior</code> , 15	<code>hashtable?</code> , 16
<code>fxlength</code> , 15	<code>i/o-decoding-error?</code> , 14
<code>fxmax</code> , 15	<code>i/o-encoding-error-char</code> , 14
<code>fxmin</code> , 15	<code>i/o-encoding-error?</code> , 14

- [i/o-error-filename](#), 14
- [i/o-error-port](#), 14
- [i/o-error-position](#), 14
- [i/o-error?](#), 14
- [i/o-file-already-exists-error?](#), 14
- [i/o-file-does-not-exist-error?](#), 14
- [i/o-file-is-read-only-error?](#), 14
- [i/o-file-protection-error?](#), 14
- [i/o-filename-error?](#), 14
- [i/o-invalid-position-error?](#), 14
- [i/o-port-error?](#), 14
- [i/o-read-error?](#), 14
- [i/o-write-error?](#), 14
- [identifier-syntax](#), 13
- [identifier?](#), 16
- [if](#), 13
- [imag-part](#), 13
- [immutable](#), 14
- [implementation-restriction-violation?](#), 14
- [inexact](#), 13
- [inexact->exact](#), 17
- [inexact?](#), 13
- [infinite?](#), 13
- [input-port?](#), 14
- [Installing Libraries](#), 6
- [integer->char](#), 13
- [integer-valued?](#), 13
- [integer?](#), 13
- [irritants-condition?](#), 14
- [lambda](#), 13
- [Language Interoperability](#), 10
- [latin-1-codec](#), 14
- [lcm](#), 13
- [least-fixnum](#), 15
- [length](#), 13
- [let](#), 13
- [let\\*](#), 13
- [let\\*-values](#), 13
- [let-syntax](#), 13
- [let-values](#), 13
- [letrec](#), 13
- [letrec\\*](#), 13
- [letrec-syntax](#), 13
- [lexical-violation?](#), 14
- [Libraries and Collections](#), 9
- [list](#), 13
- [list->string](#), 13
- [list->vector](#), 13
- [list-ref](#), 13
- [list-sort](#), 13
- [list-tail](#), 13
- [list?](#), 13
- [log](#), 13
- [lookahead-char](#), 14
- [lookahead-u8](#), 14
- [magnitude](#), 13
- [make-assertion-violation](#), 14
- [make-bytevector](#), 13
- [make-custom-binary-input-port](#), 14
- [make-custom-binary-input/output-port](#), 14
- [make-custom-binary-output-port](#), 14
- [make-custom-textual-input-port](#), 14
- [make-custom-textual-input/output-port](#), 14
- [make-custom-textual-output-port](#), 14
- [make-enumeration](#), 16
- [make-eq-hashtable](#), 16
- [make-eqv-hashtable](#), 16
- [make-error](#), 14
- [make-hashtable](#), 16
- [make-i/o-decoding-error](#), 14
- [make-i/o-encoding-error](#), 14
- [make-i/o-error](#), 14
- [make-i/o-file-already-exists-error](#), 14
- [make-i/o-file-does-not-exist-error](#), 14
- [make-i/o-file-is-read-only-error](#), 14
- [make-i/o-file-protection-error](#), 14
- [make-i/o-filename-error](#), 14
- [make-i/o-invalid-position-error](#), 14

[make-i/o-port-error](#), 14  
[make-i/o-read-error](#), 14  
[make-i/o-write-error](#), 14  
[make-implementation-restriction-violation](#), 14  
[make-irritants-condition](#), 14  
[make-lexical-violation](#), 14  
[make-message-condition](#), 14  
[make-no-infinities-violation](#), 15  
[make-no-nans-violation](#), 15  
[make-non-continuable-violation](#), 14  
[make-polar](#), 13  
[make-record-constructor-descriptor](#), 14  
[make-record-type-descriptor](#), 14  
[make-rectangular](#), 13  
[make-serious-condition](#), 14  
[make-string](#), 13  
[make-syntax-violation](#), 14  
[make-transcoder](#), 14  
[make-undefined-violation](#), 14  
[make-variable-transformer](#), 16  
[make-vector](#), 13  
[make-violation](#), 14  
[make-warning](#), 14  
[make-who-condition](#), 14  
[map](#), 13  
[max](#), 13  
[member](#), 13  
[memp](#), 13  
[memq](#), 13  
[memv](#), 13  
[message-condition?](#), 14  
[min](#), 13  
[mod](#), 13  
[mod0](#), 13  
[modulo](#), 17  
[mutable](#), 14  
[nan?](#), 13  
[native-endianness](#), 13  
[native-eol-style](#), 14  
[native-transcoder](#), 14  
[negative?](#), 13  
[newline](#), 15  
[no-infinities-violation?](#), 15  
[no-nans-violation?](#), 15  
[non-continuable-violation?](#), 14  
[nongenerative](#), 14  
[not](#), 13  
[null-environment](#), 17  
[null?](#), 13  
[number->string](#), 13  
[number?](#), 13  
[numerator](#), 13  
[odd?](#), 13  
[opaque](#), 14  
[open-bytevector-input-port](#), 14  
[open-bytevector-output-port](#), 14  
[open-file-input-port](#), 14  
[open-file-input/output-port](#), 14  
[open-file-output-port](#), 14  
[open-input-file](#), 15  
[open-output-file](#), 15  
[open-string-input-port](#), 14  
[open-string-output-port](#), 14  
[or](#), 13  
[output-port-buffer-mode](#), 14  
[output-port?](#), 14  
[pair?](#), 13  
[parent](#), 14  
[parent-rtd](#), 14  
[partition](#), 13  
[peek-char](#), 15  
[port-eof?](#), 14  
[port-has-port-position?](#), 14  
[port-has-set-port-position!?](#), 14  
[port-position](#), 14  
[port-transcoder](#), 14  
[port?](#), 14  
[positive?](#), 13  
[procedure?](#), 13  
[protocol](#), 14  
[put-bytevector](#), 14  
[put-char](#), 14



- [put-datum](#), 14
- [put-string](#), 14
- [put-u8](#), 14
- [quasiquote](#), 13
- [quasisyntax](#), 16
- [quote](#), 13
- [quotient](#), 17
- [r6rs](#), 8
- [R<sup>6</sup>RS Conformance](#), 11
- [R<sup>6</sup>RS Libraries](#), 13
- [R<sup>6</sup>RS Module Language](#), 8
- [R6RS: Scheme](#), 1
- [raise](#), 14
- [raise-continuable](#), 14
- [rational-valued?](#), 13
- [rational?](#), 13
- [rationalize](#), 13
- [read](#), 15
- [read-char](#), 15
- [real->flonum](#), 15
- [real-part](#), 13
- [real-valued?](#), 13
- [real?](#), 13
- [record-accessor](#), 14
- [record-constructor](#), 14
- [record-constructor-descriptor](#), 14
- [record-field-mutable?](#), 14
- [record-mutator](#), 14
- [record-predicate](#), 14
- [record-rtd](#), 14
- [record-type-descriptor](#), 14
- [record-type-descriptor?](#), 14
- [record-type-field-names](#), 14
- [record-type-generative?](#), 14
- [record-type-name](#), 14
- [record-type-opaque?](#), 14
- [record-type-parent](#), 14
- [record-type-sealed?](#), 14
- [record-type-uid](#), 14
- [record?](#), 14
- [remainder](#), 17
- [remove](#), 13
- [remp](#), 13
- [remq](#), 13
- [remv](#), 13
- [reverse](#), 13
- [rnrs/arithmetic/bitwise-6](#), 15
- [rnrs/arithmetic/fixnums-6](#), 15
- [rnrs/arithmetic/flonums-6](#), 15
- [rnrs/base-6](#), 13
- [rnrs/bytevectors-6](#), 13
- [rnrs/conditions-6](#), 14
- [rnrs/control-6](#), 13
- [rnrs/enums-6](#), 16
- [rnrs/eval-6](#), 16
- [rnrs/exceptions-6](#), 14
- [rnrs/files-6](#), 15
- [rnrs/hashtables-6](#), 16
- [rnrs/io/ports-6](#), 14
- [rnrs/io/simple-6](#), 15
- [rnrs/lists-6](#), 13
- [rnrs/mutable-pairs-6](#), 16
- [rnrs/mutable-strings-6](#), 16
- [rnrs/programs-6](#), 15
- [rnrs/r5rs-6](#), 17
- [rnrs/records/inspection-6](#), 14
- [rnrs/records/procedural-6](#), 14
- [rnrs/records/syntactic-6](#), 14
- [rnrs/sorting-6](#), 13
- [rnrs/syntax-case-6](#), 16
- [rnrs/unicode-6](#), 13
- [round](#), 13
- [Running Top-Level Programs](#), 5
- [scheme-report-environment](#), 17
- [sealed](#), 14
- [serious-condition?](#), 14
- [set!](#), 13
- [set-car!](#), 16
- [set-cdr!](#), 16
- [set-port-position!](#), 14
- [simple-conditions](#), 14
- [sin](#), 13
- [sint-list->bytevector](#), 13
- [sqrt](#), 13

- standard-error-port, 14
- standard-input-port, 14
- standard-output-port, 14
- string, 13
- string->bytevector, 14
- string->list, 13
- string->number, 13
- string->symbol, 13
- string->utf16, 13
- string->utf32, 13
- string->utf8, 13
- string-append, 13
- string-ci-hash, 16
- string-ci<=?, 13
- string-ci<?, 13
- string-ci=?, 13
- string-ci>=?, 13
- string-ci>?, 13
- string-copy, 13
- string-downcase, 13
- string-fill!, 16
- string-foldcase, 13
- string-for-each, 13
- string-hash, 16
- string-length, 13
- string-normalize-nfc, 13
- string-normalize-nfd, 13
- string-normalize-nfkc, 13
- string-normalize-nfkd, 13
- string-ref, 13
- string-set!, 16
- string-titlecase, 13
- string-upcase, 13
- string<=?, 13
- string<?, 13
- string=?, 13
- string>=?, 13
- string>?, 13
- string?, 13
- substring, 13
- symbol->string, 13
- symbol-hash, 16
- symbol=?, 13
- symbol?, 13
- syntax, 16
- syntax->datum, 16
- syntax-case, 16
- syntax-rules, 13
- syntax-violation, 16
- syntax-violation-form, 14
- syntax-violation-subform, 14
- syntax-violation?, 14
- tan, 13
- textual-port?, 14
- The Implementation of R<sup>6</sup>RS, 8
- transcoded-port, 14
- transcoder-codec, 14
- transcoder-eol-style, 14
- transcoder-error-handling-mode, 14
- truncate, 13
- u8-list->bytevector, 13
- uint-list->bytevector, 13
- undefined-violation?, 14
- unless, 13
- unquote, 13
- unquote-splicing, 13
- unsyntax, 16
- unsyntax-splicing, 16
- Using R<sup>6</sup>RS, 8
- Using R<sup>6</sup>RS with DrRacket, 4
- utf-16-codec, 14
- utf-8-codec, 14
- utf16->string, 13
- utf32->string, 13
- utf8->string, 13
- values, 13
- vector, 13
- vector->list, 13
- vector-fill!, 13
- vector-for-each, 13
- vector-length, 13
- vector-map, 13
- vector-ref, 13
- vector-set!, 13

- [vector-sort](#), 13
- [vector-sort!](#), 13
- [vector?](#), 13
- [violation?](#), 14
- [warning?](#), 14
- [when](#), 13
- [who-condition?](#), 14
- [with-exception-handler](#), 14
- [with-input-from-file](#), 15
- [with-output-to-file](#), 15
- [with-syntax](#), 16
- [write](#), 15
- [write-char](#), 15
- [zero?](#), 13